


Notes

1. HTR-275-31... 90-Degree Rotary Feedthrough w/Option-31, Pneumatic Actuator w/150 PSI Solenoid Valve / 30-Degree adjustable angle, both ends
2. Welded bellows sealed air-to-vacuum interface
3. Leak test to 5×10^{-10} Standard cc/sec of He
4. Maximum Load : 6lb Axial, 10lb Lateral, 250 oz-in Torque
5. Resolution : Rotary scale / 5-Degrees
6. Optional 'Speed Control Valve' kit part number 112687 (sold separately)

Rev.	Description	Date	Made By	Approval
B	Remodeled	4/16/2019	AL	

**UNCONTROLLED WEB DRAWING**

Proprietary and Confidential
The information contained in this drawing is the sole property of Accu-Glass, Products Inc. Any reproduction, in part or as whole, without the written permission of Accu-Glass Products, Inc., is strictly prohibited.

Material
See Individual Components

Tolerances,
unless otherwise specified

.X ± .030	Angles ± 0.5° Finish 63Ra
.XX ± .010	
.XXX ± .005	

Title

HTR-275-31

Drawn by
Date

Ligeti
4/16/2019

No. **102110.31**

Rev.

B

Approved

Sheet



Accu-Glass Products Inc.
25047 Anza Drive
Valencia, CA 91355
T 818-365-4215
F 818-365-7074
www.accuglassproducts.com